

METAL PERFORADO

| Código | Medida de Perforación(mm) | Distancia entre centros (mm) | % Área Libre | Calibres | | | | |
|---------------|-----------------------------|------------------------------|--------------|--------------|--------------|--------------|--------------|--------------|
| | | | | C22 0.8mm | C20 0.9mm | C18 1.2mm | C16 1.5mm | C14 1.9mm |
| E093/250 | ○ 2.4 | 6.0 | 32% | ● | ● | ● | | |
| E118/196 | ● 3.0 | 5.0 | 33% | ● | ● | ● | | |
| E118/392 | ○ 3.0 | 10.0 | 37% | ● | ● | ● | | |
| E187/250 | ○ 4.7 | 6.4 | 51% | ● | ● | ● | ● | |
| E196/275 | ● 5.0 | 7.0 | 46% | ● | ● | ● | ● | |
| E196/472 | ○ 5.0 | 12.0 | 16% | ● | ● | ● | ● | |
| E236/354 | ● 6.0 | 9.0 | 40% | ● | ● | ● | ● | |
| E236/590 | ○ 6.0 | 15.0 | 14% | ● | ● | ● | ● | |
| E314/393 | ● 8.0 | 10.0 | 58% | ● | ● | ● | ● | |
| E314/708 | ○ 8.0 | 18.0 | 18% | ● | ● | ● | ● | |
| E375/500 | ● 9.5 | 12.7 | 51% | ● | ● | ● | ● | ● |
| E375/866 | ○ 9.5 | 22.0 | 17% | ● | ● | ● | ● | ● |
| E393/550 | ○ 10.0 | 14.0 | 56% | ● | ● | ● | ● | ● |
| E393/944 | ○ 10.0 | 24.3 | 48% | ● | ● | ● | ● | ● |
| E500/687 | ● 12.7 | 17.4 | 48% | ● | ● | ● | ● | ● |
| E500/1181 | ○ 12.7 | 30.0 | 16% | ● | ● | ● | ● | ● |
| E750/1000 | ○ 19.1 | 25.4 | 51% | ● | ● | ● | ● | ● |
| E1000/1500 | ○ 25.4 | 38.08 | 40% | ● | ● | ● | ● | ● |
| SS4x20/16x24 | ○ Ancho:4.0mm Largo:20mm | W:16.0mm Y:24mm | 40% | ● | ● | | | |
| SS10x30/40x40 | ○ Ancho:10mm Largo:30mm | W:40mm Y:40mm | 15% | ● | ● | | | |
| C750-1000 | □ 19.1 | 25.4 | 55% | ● | ● | ● | ● | |

● Medidas disponibles en inventario de 2x1 en C16 y C18.

LÁMINA ANTIDERRAPANTE



A. PERFORADO
ART. 35002



A. BURBUJA
ART. 35003



A. ZARPA
ART. 35001



A. SEMILLA
ART. 35004



ALUM DIAMANTE
ART. 35008

Presentación

Tamaño

91 x 244cms
91 x 305cms
122 x 244cms
122 x 305cms
150 x 305cms

Medidas Especiales

Material

Acero al carbón
Galvanizado
Inoxidable
Aluminio
Acero Corten

Espesores

C20, C18, C16
C14, C12, C1/8